DUCT ACCESS DOORS

STANDARD SIZES

Quantity ADC	Quantity ADH	Size	Dim. A Width	Dim. B Height	Frame Neck O.D.	No. of Cams ADC	No. of Cams ADH	Option(s)
		6 x 6	6	6	4-7/8" x 4-7/8"	2	1	
		8 x 8	8	8	6-7/8" x 6-7/8"	2	1	
		10 x 10	10	10	8-7/8" x 8-7/8"	2	1	
		12 x 12	12	12	10-7/8" x 10-7/8"	2	1	
		14 x 14	14	14	12-7/8" x 12-7/8"	2	1	
		16 x 16	16	16	14-7/8" x 14-7/8"	4	2	
		18 x 18	18	18	16-7/8" x 16-7/8"	4	2	
		20 x 20	20	20	18-7/8" x 18-7/8"	4	2	
		24 x 24	24	24	22-7/8" x 22-7/8"	4	2	
		24 x 36	24	36	22-7/8" x 34-7/8"	6	3	
		30 x 30	30	30	28-7/8" x 28-7/8"	8	4	
		24 x 48	24	48	22-7/8" x 46-7/8"	8	4	
		36 x 36	36	36	34-7/8" x 34-7/8"	10	5	

Standard construction to 4.5" S.P.
High pressure construction available (see Model ADC-HP).

SPECIFICATIONS:

- DOOR PANEL: 24 ga. galvanized steel
- FRAME: 22 ga. galvanized steel
- INSULATION: 1" fiberglass
- PRE-FORMED TABS: 22 ga. galvanized steel
- CAMS & STRIKERS: galvanized steel
- HINGE: plated steel

OPTIONAL CONSTRUCTION:

- .032" aluminum with aluminum hinge and/or plated steel cams & strikers
- 24 gauge stainless steel with stainless steel hinge and/or cams & strikers

OTHER OPTIONS:

- Chain (ADC only)
- Cylinder cam lock (ADH only)
- Hasp (ADH only)
- Padlock eyes (ADH only)

TYPICAL DOUBLE PANEL ACCESS DOOR



To maintain KEES' policy of continuous product development, we reserve the right to change prices, specifications, ratings and dimensions without notice or obligation.

Project		**Location**	
Engineer			
Architect		**Dwg. No.**	**SD-ADC-H**
Contractor		**Date**	**12/11**

KEES INCORPORATED
400 S. Industrial Dr.
Elkhart Lake, WI 53020
Phone: (920) 876-3391
Fax: (920) 876-3065
Website: www.kees.com