



FHD0 - ROUND FLOOR GRILLES



STANDARD FEATURES:

- 0° blade deflection is standard, specify Model FHD0.
- All welded, heavy construction.
- 1/8" x 1/2" horizontal blades, 3/8" centers supported by vertical bars on 6" centers. Other blade / support bar spacing available.
- Countersunk screw holes, maximum 10" centers and flat head screws are standard for surface mounting.

STANDARD FINISH:


- Aluminum - mill finish or white
- Stainless steel - 304 or 316 satin finish

* 4" with optional O.B.D.

OPTIONS:


- Aluminum construction (.125")
- Stainless steel construction (12 ga.)
- Extended sleeve
- Opposed blade damper
- No screw holes
- Concealed mounting, Option G
- Two-part polyurethane white finish (stainless steel)
- Other paint finishes
- Mill finish (industrial grade) blades (stainless steel only)
- Clear or bronze anodized (aluminum only)
- Security screws

**Mounting Option G
Fastening Lugs**



Qty.	Listed Size - Diameter "D"	Damper	Screw Holes	Debris Screen	Material	Other Options	Finish	Tag

To maintain KEES' policy of continuous product improvement, we reserve the right to change prices, specifications, ratings or dimensions without notice or obligation.

Project		Location		 KEES INC. 400 S. Industrial Dr. • P.O. Box L Elkhart Lake, WI 53020 Phone: (920) 876-3391 Fax: (920) 876-3065 Website: www.kees.com	
Engineer		Dwg. No.			
Architect		SD-FHDR			
Contractor		Date			
				01/11	